






## 2 SERIES

<http://tiny.cc/multione2-2EN>


 TIPPING LOAD <b>580</b> kg	 ENGINE POWER <b>27*</b> hp	 SPEED <b>12</b> km/h	 FLOW RATE <b>42*</b> l/min	 LIFT HEIGHT <b>1,82</b> m
---	--	---	---	--

(\*) 2.3

Tires size	Width
20x8.00-10	980 mm (38.6 in)
21x8.00-10	998 mm (39.3 in)
23x8.50-12	1020 mm (40.2 in)

Model	2.2	2.3
Engine	B&S Vanguard 7220	B&S Vanguard 8270
Power (Iso Gross)	22 HP	27 HP
Fuel	Petrol	Petrol
Transmission	Hydrostatic	Hydrostatic
Drive speed (max.)	12 km/h (7.5 mph)	12 km/h (7.5 mph)
Aux. hydraulics oil flow	31 l/min (8.2 gal/min)	42 l/min (11.1 gal/min)
Max. lifting height	1,82 m (71.7 in)	1,82 m (71.7 in)
Tipping load, max <sup>(1)</sup>	580 kg (1279 lbs)	580 kg (1279 lbs)
Lifting capacity straight <sup>(2)</sup>	470 kg (1036 lbs)	470 kg (1036 lbs)
Lifting capacity fully articulated <sup>(3)</sup>	450 kg (992 lbs)	450 kg (992 lbs)
Breakout force / 50 cm (19.7 in)	500 kg (1102 lbs)	500 kg (1102 lbs)
Pushing force (c)	800 kgf (800 kp)	800 kgf (800 kp)
Specific ground pressure (w/standard tires)	593 kg/m <sup>2</sup> (121 lbs/sqft)	610 kg/m <sup>2</sup> (125 lbs/sqft)
Turning radius: inside/outside	700 / 1698 mm (27.6 / 66.9 in)	700 / 1698 mm (27.6 / 66.9 in)
Standard tires (Tractor profile)	21x8.00-10	21x8.00-10
Length	1859 mm (73.2 in)	1859 mm (73.2 in)
Height	1900 mm (74.8 in)	1900 mm (74.8 in)
Weight	680 kg (1500 lbs)	700 kg (1543 lbs)
Product Code	<b>C951021</b>	<b>C951026</b>
Price		

<sup>(1)</sup> Maximum load that can be lifted just off the ground when the machine is straight and with backweights. Weight of attachment included.

<sup>(2)</sup> Machine straight, with backweights. Weight of attachment is included. (80% of tipping load).

<sup>(3)</sup> Machine fully articulated, with backweights. Weight of attachment is included.

## 2 SERIES - FEATURES AND OPTIONS



- 4WD hydrostatic Direct Drive motors, proportional servo
- DBS (Dynamic Block System)
- Hydraulic oil cooler
- Hydraulic multiconnector
- Self-levelling H-frame boom
- 4-functions joystick
- ROPS-FOPS Level I
- 2 front working light
- Ergonomic seat with armrests and safety belt, adjustable position
- Mechanical parking brake

Options	Code	Price
Luxury cab (glass) with heating system	C885224	
Smart cabin with heating system	C885233	
Road lights, LED	C885229	
Additional working lights, LED, set of 3	C885230	
Trailer coupling	C880235	
Turf profile tires 20x8.00-10, set of 4	C885211	
Additional backweights 84 kg (185 lbs)	C880234	
Heated seat	C885225	
Driver area cover	C880049	
Left protection bar for operator	C885027	
Back up alarm	C883021	
Multiconnector to quick coupling 3 lines adapter	C880221	
Beacon light	C883039	