







## 5 SERIES

<http://tiny.cc/5seriesEN>

 TIPPING LOAD <b>1230</b> kg	 ENGINE POWER <b>28</b> hp	 SPEED <b>13</b> km/h	 FLOW RATE <b>42</b> l/min	 LIFT HEIGHT <b>2,75</b> m
--	---	---	--	--

Tires size	Width
23x8.50-12	980 mm (38.6 in)
27x8.50-15	1000 mm (39.4 in)
23x10.50-12	1090 mm (42.9 in)
26x12.00-12	1200 mm (47.2 in)

Model	5.3
Engine	Yanmar 3TNV76
Power (Iso Gross)	28 HP
Fuel	Diesel
Transmission	Hydrostatic
Drive speed (max.)	13 km/h (8.1 mph)
Aux. hydraulics oil flow	42 l/min (11.1 gal/min)
Max. lifting height	2,75 m (108 in)
Tipping load, max <sup>(1)</sup>	1230 kg (2712 lbs)
Lifting capacity straight <sup>(2)</sup>	980 kg (2160 lbs)
Lifting capacity fully articulated <sup>(3)</sup>	800 kg (1763 lbs)
Breakout force / 50 cm (19.7 in)	800 kg (1764 lbs)
Pushing force (c)	900 kgf (900 kp)
Specific ground pressure (w/standard tires)	759 kg/m <sup>2</sup> (156 lbs/sqft)
Turning radius: inside/outside	800/2000 mm (31.5/78.7 in)
Standard tires (Tractor profile)	23x10.50-12
Length	2384 mm (93.8 in)
Height	1950 mm (76,7 in)
Weight	1050 kg (2315 lbs)
Product Code	<b>C977036</b>
Price	

<sup>(1)</sup> Maximum load that can be lifted just off the ground when the machine is straight, with backweights and boom not extended. Weight of attachment included. <sup>(2)</sup> Machine straight, with backweights and boom not extended. Weight of attachment is included. <sup>(3)</sup> Machine fully articulated, with backweights and boom not extended. Weight of attachment is included.



## 5 SERIES - FEATURES AND OPTIONS



### Features

- 4WD hydrostatic Direct Drive motors, proportional servo
- Hydraulic oil cooler
- Hydraulic multiconnector
- Self-levelling double-H telescopic boom
- 11-functions joystick
- ROPS-FOPS Level I
- LCD graphic display with programmed service (tachometer, hour meter, fuel gauge, maintenance light, light indicator and other 14 indicators)
- 2 front working light
- Seat with armrests and safety belt, adjustable position
- Tipping sensor
- Mechanical parking brake
- Dynamic Block System (DBS)

## 5 SERIES - FEATURES AND OPTIONS

Options	Code	Price
Floating boom valve	C885223	
Luxury cab (glass) with inner clothing	C883510	
Heating system	C885205	
Plexiglass windscreen (smart cabin)	C883506	
Plexiglass right side (smart cabin)	C883507	
Plexiglass back window (smart cabin)	C883508	
Road lights	C883509	
3 additional working led light "Hella"	C883018	
Attachment coupling plate for rear mounting	C880031	
Multiconnector to quick coupling 3 lines adapter	C880221	
Rear 12V electric socket	C883022	
Rear hydraulic outlets - single	C883501	
Rear hydraulic outlets - double	C883502	
Additional front hydraulic outlets	C883503	
Trailer coupling	C885014	
Backweights 184 kg (92+92 kg) (203 + 203 lbs)	C880054	
Heated seat	C885216	
Left protection bar for operator	C885026	
Inner clothing for cabin	C883511	
Torque divider	C885016	
Tractor profile tires 26x12.00-12, set of 4	C885209	
Skid profile tires 27x8.50-15, set of 4	C885210	
Turf profile tires 23x8.50-12, set of 4	C885207	
Turf profile tires 26x12.00-12, set of 4	C885208	
Wheel spacer 10 mm (0,2 in)(max. 2 pcs for wheel)	C880090	
Wheel spacer 55 mm (2,2 in), set of 4	C885010	
Snow chains for wheels 23x8.50-12, set of 2	C880041	
Snow chains for wheels 23x10.50-12, set of 2	C880046	
Snow chains for wheels 26x12.00-12, set of 2	C880042	
Snow chains for wheels 27x8.50-15, set of 2	C880045	
Engine block Heater 220 V	C885250	
Engine block Heater 110 V	C885255	
Driver area cover	C880049	
Back up alarm	C883021	
Beacon light	C883039	